



Ø200 cover PVC	A	Ø160 cover Cast iron 40t	B	Ø400 cover PVC	C	Ø315 cover Cast iron 40t	D	Ø760 cover PE insulated	E	Ø630 cover Cast iron 40t	F

Volume V (m3)	Length L (mm)	Product code
1	1550	501001
2	2800	501002
3	4100	501003
4	5350	501004
5	6650	501005
6	7900	501006
7	9200	501007
8	10450	501008
9	11750	501009
10	12550	501010

Pos.	Description	Material	Size
1	Cover	PVC / PE / Cast iron	according to selection
2	Service opening	PE100	according to selection
3	Tank cylinder, double wall	PE100	ID1000, SN2
4	End cap	PE	ID1000
5	Inlet coupling	PVC	Ø110
6	Alarm device Tank-Check RF-412	-	optional

Tank volume	V=	m ³
Inlet depth from Ground Surface NB! max1,2m	H =	mm / standard 950 mm
Service opening type	A B C D E F	
Service opening location	L1 =	mm / middle
Alarm device	YES / NO	

Drawn:	A.Käärid	Underground tank ID1000 STRONG		
Approved:	J.Karolin			
www.iwsgroup.ee		Mass: kg	Product code:	Rev.
Innovative Water Systems		NA	5010 / ordersheet	0